

	CO-ORDINATION OF NOTIFIED BODIES PPE-Directive 89/686/EEC + amendments RECOMMENDATION FOR USE	CNB/P/07.008 Revision Language: E
Number of pages: 1	Date: 23/3/2005	Approval by : _____ Approved on : _____
Origin : Vertical Group 7 'Protective Clothing against Hand-held Chain Saws'		<input checked="" type="checkbox"/> Vertical Group17/10/1997..& on the.....23/03/2005..... <input checked="" type="checkbox"/> Horizontal Committee15/06/2011..... <input type="checkbox"/> Standing Committee
Question related to:	EN/prEN: 381	Other: _____
Annex: _____ Article: _____	Clause: _____	
Key words: Uncertainty of measurement		
Question: How should the measurement of uncertainty be taken into account?		
Solution: In EN 381-1, when calibrating the chain, at least 8 layers of the calibration pad shall be cut-through at 19 m/s. At 21 m/s the hole in the last layer shall be more than 10 mm (but not significantly more).		
Sent for information to: <input checked="" type="checkbox"/> members of the VG <input type="checkbox"/> other(s) VG <input checked="" type="checkbox"/> HC (2) <input type="checkbox"/> TC (3) <input type="checkbox"/> SC (4) <input type="checkbox"/> other (5) (3): _____ (5): _____		

(1) Essential safety requirement
 (2) HC = horizontal committee

(3) N° of CEN/TC (Secretary & Chairman)
 (4) EEC Standing Committee 89/392

(5) To be specified