

CO-ORDINATION OF NOTIFIED BODIES PPE-Directive 89/686/EEC + amendments

CNB/P/10.078 Revision 01 Language: E

* * *	RECOMMENDATION FOR USE		
Number of pages: 1	Date: 01/10/03	Approval by :	Approved on :
Origin: CTC		✓ Vertical Group✓ Horizontal Committee✓ Standing Committee	
Question related to: Directive 89/686/EEC		EN/prEN: 20344 20345 etc	Other:
Annex:	Article:	Clause:	
Key words: upper material to test			
Question:			
In the model shown, a textile material (insert) covers the upper. This textile is a high visibility material. It is here to increase the safety properties of the footwear. EN ISO 20345/20346 in the table 7(table 5 in EN ISO 20347), define the line under which the upper component shall be fulfilled. Do we have to consider this polymeric area has a part of the upper?			
Solution:			
The insert shall fulfil the requirement of EN ISO 20345/20346/20347: - the upper requirements if it is located under the minimum height defined in table 7 (EN ISO 20345/20346) and table 5 (EN ISO 20347) - the lining requirements (tear strength and abrasion resistance) if it is located over the minimum height defined in table 7 (EN ISO 20345/20346) and table 5 (EN ISO 20347); Sent to: members of the VG □ other(s) VG ☑ HC (2) ☑ TC (3) □ SC (4) □ other (5)			
Sent to: 🛛 member	rs of the VG		C (4)