



CO-ORDINATION OF NOTIFIED BODIES
PPE-Directive 89/686/EEC + amendments

CNB/P/10.101
Revision 01
Language: E

RECOMMENDATION FOR USE

Number of pages: 1	Date: 25/04/06	Approval by :	Approved on :
Origin: INESCOP		<input checked="" type="checkbox"/> Vertical Group	24/03/06
		<input checked="" type="checkbox"/> Horizontal Committee	13/09/11
		<input type="checkbox"/> Standing Committee	
Question related to: Non-cleated outsoles	EN ISO 20344,5,6,7	Other:	
Annex:	Article:	Clause:	
Key words: Slip resistance & non-cleated outsoles			
Question: RU 10.044 recommends to consider an outsole with cleat height less than 2,5 mm as not cleated, specifying this in the certificate. This could be not sufficient, because the height could be only 0,5 mm and become worn out very quickly. The slip resistance would change significantly.			
Solution: In this case it was agreed that it was particularly important for the user information to explain the possible effect of worn cleats on slip resistance and to include a warning for the user to examine the cleats before use.			
Sent to: <input checked="" type="checkbox"/> members of the VG <input type="checkbox"/> other(s) VG <input type="checkbox"/> HC (2) <input checked="" type="checkbox"/> TC (3) <input type="checkbox"/> SC (4) <input type="checkbox"/> other (5)			

(1) Essential safety requirement
(2) HC = horizontal committee

(3) N° of CEN/TC (Secretary & Chairman)
(4) EEC Standing Committee 89/392

(5) To be specified