



CO-ORDINATION OF NOTIFIED BODIES  
PPE-Directive 89/686/EEC + amendments

CNB/P/10.122  
Revision 01  
Language: E

RECOMMENDATION FOR USE

Number of pages: 1	Date: 29/02/08	Approval by :	Approved on :
Origin: INESCOP		<input checked="" type="checkbox"/> Vertical Group	29/02/08
		<input checked="" type="checkbox"/> Horizontal Committee	13/09/11
		<input type="checkbox"/> Standing Committee	
Question related to:	EN ISO	Other:	
Annex:	Article:	Clause:	
Key words: 5.1.7.2.1 (Ankle protection)			
Question: Paragraph 5.17.2.1 says that the drop height must be approximately 0,2 m to ensure a kinetic energy of 10 J. Should this distance be maintained constant or should it be corrected with the test piece thickness?			
Solution: The important parameter is the 10 J impact energy (For instance as calculated from the speed measured just prior to the impact). Hence the drop height should be adjusted to always give a 10 J impact energy.			
Sent to: <input checked="" type="checkbox"/> members of the VG <input type="checkbox"/> other(s) VG <input checked="" type="checkbox"/> HC (2) <input type="checkbox"/> TC (3) <input type="checkbox"/> SC (4) <input type="checkbox"/> other (5)			

(1) Essential safety requirement  
(2) HC = horizontal committee

(3) N° of CEN/TC (Secretary & Chairman)  
(4) EEC Standing Committee 89/392

(5) To be specified